

EN & DIN Bellows seal globe valve Straight way with Flange

Size	15	20	25	32	40	50	65	80	100	125	150	200	250	300	350	400	
L	130	150	160	180	200	230	290	310	350	400	480	600	730	850	980	1100	
H(closed)	196	196	205	205	222	224	240	265	350	380	410	550	715	790	950	1030	
Stroke	8	8	10	10	15	16	18	22	28	34	40	60	75	85	100	115	
Weight (kg)	PN16	4.2	4.7	5.6	7.5	9.5	11.9	17.4	23	36	56.2	78.8	154	238	339	610	940
	PN25	4.2	4.7	5.6	7.5	9.5	11.9	18.4	25.3	38.2	62	86	169	260	370	663	982
	PN40	4.2	4.7	5.6	7.5	9.5	11.9	18.4	26.0	38.0	64.0	87.0	178.0	283.0	398.0	690.0	1039
KV	4.2	7.4	12.0	19.0	30.0	47.0	77.0	120.0	188.0	288.0	410.0	725.0	1145.0	1635.0	2225	2906	
Main components materials																Standard	
Body	Bonnet		Bellow	Bolt	Nut	Packin g	Gasket	Sealing face		Sutiabl e medium	Suitable temp	Design					
GS-C25/GS-C25N/GP240GH/1.0619	GS-C25/GS-C25N/GP240GH/1.0619		SS304	Y	YK	Graphi te	SS304+ Graphi te	13Cr/13Cr 13Cr/STL STL/STL		WATER OIL、 GAS STEAM	≤350℃	EN13709					
												F-F					
1.4308	1.4308		SS304	0Cr18 Ni9	0Cr18 Ni9	PTFE/ Grapth ite	SS304+ Graphi te/ PTFE	304/304 STL/304 STL/STL		Corrosi ve Media	≤200℃	EN558-1/DIN 3202F1					
												Flange					
1.4408	1.4408		ss316L	0Cr18 Ni9	0Cr18 Ni9	PTFE/ Grapth ite	SS304+ Graphi te/ PTFE	316/316 STL/316 STL/STL		Corrosi ve Media	≤200℃	EN1092					
												Test					
												EN12266					