

EN & DIN Y-strainer with Flange

Executive standard

Face to face: DIN3202-F1

Flange end: DIN2531-2545

Size	15	20	25	32	40	50	65	80	100	125	150	200	250	300	350	400	
L	130	150	160	180	200	230	290	310	350	400	480	600	730	850	980	1100	
H	85	95	110	125	145	155	170	205	230	270	318	400	555	620	700	820	
H1	93	115	134	157	193	200	225	255	300	355	407	520	780	900	985	1120	
Weight (kg)	PN16	2.8	3.8	5.3	7.2	9	11.8	16.2	22.4	35	45.4	62	132	220	330	540	830
	PN25	2.8	3.8	5.3	7.2	9	11.8	16.8	24.0	38.8	50.1	68	142.6	233.4	350	574	875
	PN40	2.8	3.8	5.3	7.2	9	11.8	17.4	24.6	39.7	52.5	70.4	153	250	360	614	940
KV	6.3	11	17.5	28	44	69	118	178	270	420	620	1100	1700	2500	3400	4400	
Main components materials																Standard	
Body/Bonnet		Spring		Bolt		Gasket		Sealing face		Suitable medium		Suitable temp		Design			
GS-C25/GS-C25N/GP240GH/ 1.0619		SS304		5.8		SS304+ Graphite		SS304		Water Oil Gas Steaw		≤425°C		MEF S" Standard			
														F-F			
1.4308		SS304		0Cr18Ni9		SS304+ Graphite /PTFE		SS304		Corrosive Media		≤200°C		EN558-1/DIN3202			
														F1 Flange			
1.4408		SS316		0Cr18Ni9		SS304+ Graphite /PTFE		SS316L		Corrosive Media		≤200°C		EN1092			
														Test			
														EN12266			